


15" TFT LCD MONITOR ORION

Model: TFT1510KT

Special features		Technical specifications																																																			
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Matrix type</td><td>TFT LCD</td></tr> <tr><td>Screen size</td><td>15"</td></tr> <tr><td>Visible part of the screen</td><td>304,128x228,096mm</td></tr> <tr><td>Pixel distance</td><td>0,297mm</td></tr> <tr><td>Brightness</td><td>250Cd/m2</td></tr> <tr><td>Contrast</td><td>400:1</td></tr> <tr><td>Viewing angle</td><td>150 (H) / 140 (V)</td></tr> <tr><td>Reaction time</td><td>4/12ms</td></tr> <tr><td>Resolution (max.)</td><td>1024 x 768@75Hz</td></tr> <tr><td>Video input system</td><td>Analog RGB/(15 pin D-sub)</td></tr> <tr><td>Interface</td><td>Analog</td></tr> <tr><td>Frequency (H)</td><td>30 ~ 60kHz</td></tr> <tr><td>Frequency (V)</td><td>55 ~ 75kHz</td></tr> <tr><td>Color depth</td><td>16 700 000</td></tr> <tr><td>AC adapter</td><td>~ 100V - 240V (50/60Hz)/ = +12V 3,3A</td></tr> <tr><td>OSD menu functions number</td><td>15 ~ 25</td></tr> <tr><td>Power consumption</td><td><30W</td></tr> <tr><td>Built-in speakers (Optional)</td><td>+</td></tr> <tr><td>Power control</td><td>VESA DPMS</td></tr> <tr><td>Mounting possibility</td><td>VESA 75mm</td></tr> <tr><td>Surrounding temperature</td><td>+5 ~ +40degrees</td></tr> <tr><td>Surrounding moisture</td><td>10 - 85%</td></tr> <tr><td>Surrounding pressure</td><td>86 ~ 104kPa</td></tr> <tr><td>Colour</td><td>Silver&Black&Ivory</td></tr> <tr><td>Safety and correspondence standards</td><td>UL,TC099,CE,FCC,CB</td></tr> </table>		Matrix type	TFT LCD	Screen size	15"	Visible part of the screen	304,128x228,096mm	Pixel distance	0,297mm	Brightness	250Cd/m2	Contrast	400:1	Viewing angle	150 (H) / 140 (V)	Reaction time	4/12ms	Resolution (max.)	1024 x 768@75Hz	Video input system	Analog RGB/(15 pin D-sub)	Interface	Analog	Frequency (H)	30 ~ 60kHz	Frequency (V)	55 ~ 75kHz	Color depth	16 700 000	AC adapter	~ 100V - 240V (50/60Hz)/ = +12V 3,3A	OSD menu functions number	15 ~ 25	Power consumption	<30W	Built-in speakers (Optional)	+	Power control	VESA DPMS	Mounting possibility	VESA 75mm	Surrounding temperature	+5 ~ +40degrees	Surrounding moisture	10 - 85%	Surrounding pressure	86 ~ 104kPa	Colour	Silver&Black&Ivory	Safety and correspondence standards	UL,TC099,CE,FCC,CB
Matrix type	TFT LCD																																																				
Screen size	15"																																																				
Visible part of the screen	304,128x228,096mm																																																				
Pixel distance	0,297mm																																																				
Brightness	250Cd/m2																																																				
Contrast	400:1																																																				
Viewing angle	150 (H) / 140 (V)																																																				
Reaction time	4/12ms																																																				
Resolution (max.)	1024 x 768@75Hz																																																				
Video input system	Analog RGB/(15 pin D-sub)																																																				
Interface	Analog																																																				
Frequency (H)	30 ~ 60kHz																																																				
Frequency (V)	55 ~ 75kHz																																																				
Color depth	16 700 000																																																				
AC adapter	~ 100V - 240V (50/60Hz)/ = +12V 3,3A																																																				
OSD menu functions number	15 ~ 25																																																				
Power consumption	<30W																																																				
Built-in speakers (Optional)	+																																																				
Power control	VESA DPMS																																																				
Mounting possibility	VESA 75mm																																																				
Surrounding temperature	+5 ~ +40degrees																																																				
Surrounding moisture	10 - 85%																																																				
Surrounding pressure	86 ~ 104kPa																																																				
Colour	Silver&Black&Ivory																																																				
Safety and correspondence standards	UL,TC099,CE,FCC,CB																																																				
<ul style="list-style-type: none"> * High-performance intelligent multi-scanning color monitor * Modern design and dimensions * Auto color balance * Power saving compliant * Built-in speakers * Plug & Play * Capability of hanging up on the wall 																																																					
Complement		Dimensions																																																			
<ul style="list-style-type: none"> * Monitor with table stand * AC adapter 100V-240V/12V * Audio cable (Optional) * Driver * VGA cable * User's Manual * Warranty card 	<ul style="list-style-type: none"> 1pc 1pc 1pc 1pc 1pc 1pc 1pc 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Unit dimensions, MM</td><td>350x360x150</td></tr> <tr><td>Box dimensions, MM</td><td>395x418x165</td></tr> <tr><td>Package dimensions, MM</td><td>395x418x165</td></tr> <tr><td>Package dimensions, M3</td><td>0,027</td></tr> <tr><td>Number of boxes in package, pc</td><td>1</td></tr> <tr><td>Weight (unit), kg</td><td>3,5</td></tr> <tr><td>Weight (package), kg</td><td>5</td></tr> </table>		Unit dimensions, MM	350x360x150	Box dimensions, MM	395x418x165	Package dimensions, MM	395x418x165	Package dimensions, M3	0,027	Number of boxes in package, pc	1	Weight (unit), kg	3,5	Weight (package), kg	5																																				
Unit dimensions, MM	350x360x150																																																				
Box dimensions, MM	395x418x165																																																				
Package dimensions, MM	395x418x165																																																				
Package dimensions, M3	0,027																																																				
Number of boxes in package, pc	1																																																				
Weight (unit), kg	3,5																																																				
Weight (package), kg	5																																																				